

• **ANNEX II + III/ ANEKS II+III: TECHNICAL SPECIFICATIONS + TECHNICAL OFFER / TEHNIČKA SPECIFIKACIJA + TEHNIČKA PONUDA**

Contract title/ Naziv ugovora: Supply contract for search and rescue equipment / Ugovor o nabavci opreme za potragu i spasavanje

p 1 /...

Publication reference/ Broj nabavke: 11-404-1-7/22

Columns 1-2 should be completed by the contracting authority / Kolonu 1-2 treba popuniti ugovorno tijelo

Columns 3-4 should be completed by the tenderer / Ponuđač treba popuniti kolone 3-4

Column 5 is reserved for the evaluation committee / Kolona 5 rezervirana je za ocjenjivačko povjerenstvo

Annex III - the contractor's technical offer / Prilog III - tehnička ponuda izvođača

The tenderers are requested to complete the template on the next pages: / Mole se ponuđači da popune obrazac na sljedećim stranicama:

- Column 2 is completed by the contracting authority shows the required specifications (not to be modified by the tenderer), / Kolonu 2 popunjava ugovorno tijelo - iskazuje tražene specifikacije (ne mijenja se od strane ponuđača),
- Column 3 is to be filled in by the tenderer and must detail what is offered (for example the words 'compliant' or 'yes' are not sufficient) / Kolonu 3 mora ispuniti ponuđač i mora navesti što se nudi (na primjer, riječi "usklađeno" ili "da" nisu dovoljne)
- Column 4 allows the tenderer to make comments on its proposed supply and to make eventual references to the documentation / Kolona 4 omogućuje ponuđaču da da komentare na svoju predloženu ponudu i eventualne reference na dokumentaciju

The eventual documentation supplied should clearly indicate (highlight, mark) the models offered and the options included, if any, so that the evaluators can see the exact configuration. Offers that do not permit to identify precisely the models and the specifications may be rejected by the evaluation committee. / Eventualna isporučena dokumentacija treba jasno naznačiti (istaknuti, označiti) ponuđene modele i uključene opcije, ako ih ima, tako da ocjenjivači mogu vidjeti točnu konfiguraciju. Ponude koje ne dopuštaju precizno identificiranje modela i specifikacija mogu biti odbijene od strane Komisije za ocjenjivanje

The offer must be clear enough to allow the evaluators to make an easy comparison between the requested specifications and the offered specifications. / Ponuda mora biti dovoljno jasna da ocjenjivačima omogućujući jednostavnu usporedbu između traženih i ponuđenih specifikacija.

MOLIMO DA PONUDU ODŠTAMPATE U BOJI ZBOG FOTOGRAFIJA PONUĐENIH ARTIKALA

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
1	<p><u>Diving suit - wet - 4 pcs</u></p> <ul style="list-style-type: none"> ● Material: stretchable N2S environmentally friendly 7 mm X-Foam neoprene or equivalent ● Diagonal front zipper with metal slider ● Wrist and arm seals with zippers ● Strong knee pads and material on the shoulders and seat region ● Color Black <p><u>Ronilačko odijelo – mokro - 4 komada</u></p> <ul style="list-style-type: none"> ● Materijal: rastezljiv N2S ekološki prihvatljiv 7 mm X-Foam neopren ili ekvivalent ● Dijagonalni prednji patent zatvarač sa metalnim klizačem ●Brtve na ručnim zglobovima i na rukama sa patentnim zatvaračima ● Jaki jastučići za koljena i materijal na ramenima i sjedalnoj regiji ● Boja Crna 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
2.	<p><u>Diving suit dry + integrated boot - 3 pcs</u></p> <ul style="list-style-type: none"> • T-cut, telescopic torso, BDM or TIZIP patent or equivalent, front and shoulders with X-treme protection, protection patent over the main part, neoprene neck cuff protection. Cordura reinforcements on leaves, knees, buttocks and forearms, EX expandable pockets. • Inner shoulder straps and elastic waist, latex cuffs on neck and arms, inner seams sealed with polymer coating • Neoprene semi-rigid Hyper-sole boots or equivalent that are integrated with the suit. Si Tech or Apex valves or equivalent. Transport bag and 5mm hood. • Material: poly / butyl / poly trilaminate mixture and seam assembly - adhesive - waterproof tape • Color Black <p><u>Ronilačko odijelo suho+ integrisana čizma - 3 kom</u></p> <ul style="list-style-type: none"> • T – kroj, teleskopski torzo, BDM ili TIZIP patent ili ekvivalent, prednjica i ramena sa X-treme zaštitom, zaštitni patent preko glavnog dijela, neoprenska zaštita vratne manžete. Kordura pojačanja na listovima, koljenima, stražnjici i podlakticama, EX raširivi džepovi. • Unutarnje naramenice i elastični struk, od lateksa manžeta na vratu i rukama, unutarnji šavovi brtvljeni polimernim premazom • Neoprenske polutvrde Hiper-sole čizmice ili ekvivalent koje su integrisane sa odijelom. Si Tech ili Apeks ventili ili ekvivalent. Transportna torba i 5mm kapuljača. • Materijal: mješavina poli / butil /poli trilaminata i sklopom šava - ljepila- vodootporne trake • Boja Crna 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
3.	<p><u>Diving podium dry - 3 pieces</u></p> <ul style="list-style-type: none"> ● Fleece double material 629 g / m2 (+/- 10%) or equivalent ● Compatible with trilaminate dry suits ● Design with compression protection on shoulders, chest, knees ● Pockets with zippers ● Elastic loops for ankles and heel ● Front double slide fastener ● Color black <p><u>Ronilačko pododijelo suvo - 3 komada</u></p> <ul style="list-style-type: none"> ● Dvostruki materijal od flisa 629 g / m2 (+/- 10%) ili ekvivalent ● Kompatibilno sa trilaminatnim suhim odijelima ● Dizajn sa zaštitom od kompresije na ramenima, prsima, koljenima ● Džepovi sa patentnim zatvaračima ● Elastične petlje za zglobove i pete ● Prednji dvostruki klizni zatvarač ● Boja crna 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
4.	<p><u>Diving boots - 4 pairs</u></p> <ul style="list-style-type: none"> ● Material: neoprene 5 - 6 mm or equivalent, with zipper for cold water ● Anti-slip sole ● Toe cap with protective cushion ● The heel cap includes a fin strap holder ● Long zipper ● Securing with velcro tab ● Color Black <p><u>Ronilačke čizme - 4 para</u></p> <ul style="list-style-type: none"> ● Materijal: neopren 5 – 6 mm ili ekvivalen, sa patent zatvaračem za hladnu vodu ● Potplat sa petom za sprečavanje klizanja ● Kapica na nožnim prstima sa zaštitnim jastukom ● Kapica na peti uključuje držač remena za peraje ● Dugi patentni zatvarač ● Osiguranje jezičkom na čičak ● Boja Crna 			
5	<p><u>Diving gloves - 4 pairs</u></p> <ul style="list-style-type: none"> ● Cold water glove 5 mm thick, contoured, double seal for optimal water blocking ability ● Anti-slip material ● Plush drying interior ● Double wrist gasket ● Glove hook ● Composition: 90% neoprene, 10% nylon. <p><u>Ronilačke rukavice - 4 para</u></p> <ul style="list-style-type: none"> ● Rukavica za hladnu vodu debljine 5 mm konturnog oblika, dvostrukog zaptivanja za optimalnu sposobnost blokiranja vode ● Materijal protiv klizanja ● Plišani enterijer koji se suši ● Dvostruka brtva za zglobove ● Kuka za spajanje rukavica ● Sastav: 90% neopren, 10% najlon. 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
6.	<p><u>Diving mask - 4 pieces</u></p> <ul style="list-style-type: none"> ● Single frameless lens design - expansive field of view with reduced volume ● Silicone tape base, headband wide <p>Double sealing</p> <ul style="list-style-type: none"> ● Wide adjustable headband ● Button clasps are attached to the tabs ● Protective box <p>Color black</p> <ul style="list-style-type: none"> ● 1 M , 1 L i 2 XL <p><u>Ronilačka maska - 4 komada</u></p> <ul style="list-style-type: none"> ● Dizajn sa jednim sočivom bez okvira - ekspanzivno vidno polje uz smanjenje volumena ● Osnova silikonska traka, traka za glavu široka ● Dvostruke brtvljenje ● Široka traka za glavu na podešavanje ● Kopče sa dugmadima pričvršćene su na jezičke ● Zaštitna kutija ● Boja crna ● 1 M , 1 L i 2 XL 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
7.	<p><u>Diving fins - 4 pairs</u></p> <ul style="list-style-type: none"> ● Material: thermoplastic ● Length: 38 cm ● Color: black ● Weight: 90g ● Open heel <p>A heel strap with a spring with a hole at the end of the blade must allow the diver to attach the fins to his suit with a strap or hook.</p> <p><u>Ronilačke peraje - 4 para</u></p> <ul style="list-style-type: none"> ● Materijal: termoplastika ● Dužina: 38 cm ● Boja: crna ● Masa: 90g ● Otvorena peta ● Remen za petu sa oprugom sa rupicom na kraju oštice mora omogućavati da ronilac remenom ili kukom prikvači peraje na svoje odijelo. 			
8.	<p><u>Weight belt - 4 pieces</u></p> <ul style="list-style-type: none"> ● Standard weight belt with stainless steel buckle ● Material: textile ● Length: 137 - 150 cm <p><u>Pojas za tegove - 4 komada</u></p> <ul style="list-style-type: none"> ● Standardni pojas za tegove sa inox kopčom ● Materijal: tekstil ● Dužina: 137 - 150 cm 			
9.	<p><u>Rubber belt weights - 20 pieces</u></p> <ul style="list-style-type: none"> ● weight 1 kg ● dimension: 8 x 6,5 x 3,5cm. <p><u>Gumirani tegovi za pojas - 20 komada</u></p> <ul style="list-style-type: none"> ● težina 1 kg ● dimenzije: 8 x 6,5 x 3,5cm. 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
10	<p><u>Diving bottle - 4 pieces</u></p> <ul style="list-style-type: none"> ● Diving bottle 10 L ● Valve certified for: 232 bar ● Material: steel with anti-corrosion protection ● double valve group; ● Cert .: EN 1964-1: 1999 and PED 97/23 / EC or equivalent ● carrying handle ● PVC feet ● safety nets ● Height without valve: 62.5 cm. ● Height with valve: 78 cm. Diameter: 20.3 cm. <p><u>Ronilačka boca - 4 komada</u></p> <ul style="list-style-type: none"> ● Ronilačka boca 10 L ● Ventil certifikovan za : 232 bar ● Materijal: čelik sa antikorozivnom zaštitom ● dupla ventilska grupa; ● cert.: EN 1964-1:1999 i PED 97/23/EC ili ekvivalent ● ručka za nošenje ● PVC stope ● zaštitne mreže ● Visina bez ventila: max 62,5 cm. ● Visina s ventilom: max 78 cm.Promjer: 20,3 cm. 			

11	<p><u>Buoyancy compensator - 4 pieces</u></p> <ul style="list-style-type: none"> • Material: 1000 den nylon and 420 den nylon - Cordura 420 or equivalent • Soft neoprene roll around the neck and padded back pad • Integrated quick-release bags secured with low-profile buckles • Two rear liner bags <p>2 SLS weight pockets with visual confirmation of correct insertion.</p> <ul style="list-style-type: none"> • Six 40 mm stainless steel D-rings, plus two additional 25 mm D-rings on the pockets • Ergonomic belt design with rotating buckles • Reinforced soft backpack with tank lid with large handle and inner lining • Stainless steel tank strap system is placed lower and joined with another strap to secure the tank for transport and diving <p>50 mm waist belt with lightweight plastic buckle Two large zipped pockets anatomical design Maximum load 6 kg / 13 lbs 3 pcs L to XL and 1 pc S / M Weight: S / M: 4.4 KGM and L / XL: 4.5 KGM knife attachment CE - EN1809: 2014 + A1: 2016 or equivalent</p> <p><u>Kompenzator plovnosti - 4 komada</u></p> <ul style="list-style-type: none"> • Materijal: najlon od 1000 den i najlon od 420 den - Cordura 420 ili ekvivalent • Mekana neoprenska rola oko vrata i obložena stražnja podloga • Integrisane vrećice sa brzim oslobađanjem učvršćene niskoprofilnim kopčama • Dvije stražnje torbice za obloge • 2 SLS džepa s utezima uz vizualnu potvrdu ispravnog umetanja. • Šest D-prstenova od nehrđajućeg čelika od 40 mm, plus dva dodatna D-prstena od 25 mm na džepovima • Ergonomski dizajn remena sa rotirajućim kopčama • Ojačani mekani ruksak sa poklopcem spremnika sa velikim rukohvatom i unutrašnjim oblogama • Sistem vrpce spremnika od nehrđajućeg čelika postavljen je niže i udružen sa drugom trakom kako bi osigurao spremnik za transport i ronjenje • Remen za struk od 50 mm s laganom plastičnom kopčom • Dva velika džepa sa patentnim zatvaračem 			
----	--	--	--	--

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
	<ul style="list-style-type: none"> ● anatomski dizajn ● Maksimalno opterećenje 6 kg / 13 lbs ● 3 kom L do XL i 1 kom S/ M ● Težina: S/M: 4,4 KGM I L/XL: 4,5 KGM ● pričvršćenje za nož ● CE– EN1809:2014+A1:2016 ili ekvivalent 			

2	<p><u>Diving regulator set - 4 pieces</u></p> <ul style="list-style-type: none"> ● PATENTED XTIS (EXTENDED THERMAL INSULATING SYSTEM) - Thermal insulation (XTIS) system or equivalent ● Movable stainless steel ring for easy opening ● COLD WATER CERTIFICATE - EN250-2014 standard for use in cold waters ● configurations - 232 bar INT ● Weight: INT 232 - 670g; ● Air flow at 200 bar (l / m): 3000 ● Mean pressure (psi / bar): 9.5-10. ● Weight (without mouthpiece): 178 g ● Air flow at 200 bar: 1400 l / min ● Soft and firm mouthpiece Comfo-Bite or equivalent ● Polyurethane valve ● Adjustable stainless steel crown ● Polyurethane cover ● Unbalanced valve mechanism behind the regulator ● Hose length: 730 mm <p><u>Ronilački regulatorni set - 4 komada</u></p> <ul style="list-style-type: none"> ● PATENTED XTIS (EXTENDED THERMAL INSULATING SYSTEM) - Termo izolacioni (XTIS) sistem ili ekvivalent ● Pokretni inox prsten za lakše otvaranje ● CERTIFIKAT ZA KORIŠĆENJE U HLADNIM VODAMA - EN250-2014 standard za korišćenje u hladnim vodama ● konfiguracijama - 232 bar INT ● Težina: INT 232 - 670g; ● Protok vazduha pri 200bara (l/m): 3000 ● Srednji pritisak (psi/bar): 9.5-10. ● Težina (bez usnika): 178 g ● Protok vazduha pri 200bara: 1400 l/min ● Mekan i čvrst usnik Comfo-Bite ili ekvivalent ● Ventil od poliuretana ● Podesiva krunica od inoksa ● Poklopac od poliuretana ● Neuravnoteženi mehanizam ventila iza regulatora ● Duljina crijeva: 730 mm 			
13	<p><u>Manometer - 4 pieces</u></p> <ul style="list-style-type: none"> ● Compact, analog manometer ● Overpressure valve ● Red zone in steps between 50 and 0 bar and 10 bar 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
	<ul style="list-style-type: none"> ● Maximum depth: 150m ● Maximum operating pressure: 400 bar <u>Manometar - 4 komada</u> <ul style="list-style-type: none"> ● Kompaktan, analogni manometar ● Ventil za preveliki pritisak ● Crvena zona u koracima između 50 i 0 bara i 10 bara ● Maksimalna dubina: 150m ● Maksimalni radni pritisak: 400 bara 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
14	<p><u>Diving lamp- 4 pcs</u></p> <ul style="list-style-type: none"> • Dimensions: 253x45 mm. • Weight (with battery): 522 g • Robust aluminum housing • Equipped with Cree XPL LED or equivalent • 850 lumens illumination. • 17,000 lux per 1m. • Color temperature: 4200 K • Beam angle: 8° • Double O-ring seals • Switch with button at the end of the light • Security lock mode with button switch • Extended headlight cover • Depth of 150 m • 3 x disposable / rechargeable C-cell batteries • Operating time: up to 7 hours at full power <p><u>Ronilačka lampa - 4 komada</u></p> <ul style="list-style-type: none"> • Dimenzije: 253x45 mm. • Težina (sa baterijom): 522 g • Robusno aluminijsko kućište • Opremljena Cree XPL LED ili ekvivalent • Osvjetljenje od 850 lumena. • 17.000 luksa na 1m. • Temperatura boje: 4200 K • Ugao snopa: 8° • Dvostruke brtve sa O-prstenom • Prekidač sa dugmetom na kraju svjetla • Režim sigurnosne brave pomoću prekidača sa dugmetom • Prošireni pokrivač svjetlosne glave • Dubina od 150 m • 3 x jednokratne / punjive baterije sa C-ćelijama • Vrijeme rada: do 7 sati pri punoj snazi 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
15	<p><u>Diving computer - 4 pieces</u></p> <ul style="list-style-type: none"> ● ZHL16 ADT MB multi-gas predictive algorithm receives three gases (21-100% O2) or equivalent ● Maximum working depth: 120m ● Altimeter ● Digital compass, shown in the bottom row ● Active backlight ● Complete clock functions ● Label function ● Protective lens cap ● Replaceable battery CR2450 service life of at least two years / 300 dives <p><u>Ronilački kompjuter - 4 komada</u></p> <ul style="list-style-type: none"> ● Prediktivni algoritam sa više gasova ZHL16 ADT MB prima tri plina (21-100% O2) ili ekvivalent ● Maksimalna radna dubina: 120m ● Visinomjer ● Digitalni kompas, prikazan u donjem redu ● Aktivno pozadinsko svjetlo ● Kompletne funkcije sata ● Funkcija oznaka ● Zaštitna kapica sočiva ● Zamjenjiva baterija CR2450 radni vijek minimalno do dvije godine / 300 zarona 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
16.	<p><u>Diving compressor - 1 piece</u></p> <ul style="list-style-type: none"> ● Flow 140 L / min ● Operating pressure 330 bar ● Single-phase motor 230V, 50Hz ● Power 3 kW ● Weight 52 kg ● Dimensions 66x40x42 cm ● Purification system P21 <p><u>Ronilački kompresor - 1 komad</u></p> <ul style="list-style-type: none"> ● Protok 140 L/min ● Operativni pritisak 330 bar ● Monofazni motor 230V, 50Hz ● Snaga 3 kW ● Težina 52 kg ● Dimenzije 66x40x42 cm ● Sistem purifikacije P21 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
17.	<p><u>Boat for 8 people - 1 PCS</u></p> <ul style="list-style-type: none"> ● Material: polyethylene ● made of one piece and has side benches inside the cockpit which form U-shaped benches with the bow part. ● length 4.35 m, width 1.73 m, ● weight 184 kg, ● load capacity CE cat. C 8 persons, cat. ● permissible weight C; 690 kg / 1521 lbs ● max engine power 30 hp long axle, ● stainless steel plate on the stern, ● holding rope-handrail, ● bow tank with lid, ● storage seat <p><u>Čamac za 8 osoba - 1 komad</u></p> <ul style="list-style-type: none"> ● Materijal: polietilen ● izrađen iz jednog komada te unutar kokpita ima bočne klupice koje s pramčanim dijelom čine klupe U oblika. ● dužina 4,35 m, širina 1,73 m, ● težina 184 kg, ● nosivost CE kat.C 8 osoba, kat. ● dozvoljena težina C; 690 kg / 1521 lbs ● max snaga motora 30 ks duga osovina, ● inox ploča na krmenom dijelu, ● konopac za držanje-rukohvat, ● pramčani spremnik sa poklopcem, ● sjedalo sa spremištem 			

18.	<p><u>Outboard motor - 1 piece</u></p> <ul style="list-style-type: none"> ● 4-stroke engine type; ● Engine capacity 747 cm3 ● Number of cylinders and layout - In-line 3 cylinders ● Diameter and stroke - 65.0 mm X 75.0 mm ● Engine power - 29.4 KW / 5,500 rpm ● Maximum throttle / engine speed - 6,000 rpm ● Engine lubrication - Wet sump ● Fuel supply - EFI ● Ignition system - CDI ● Engine start system - Electro start ● Gear ratio - 2.0 (26/13) ● Shaft - S: 414 mm L 563 mm ● Total weight with propeller - 102 kg ● Oil capacity - 1.7 liters ● Control command - Swivel handle ● Throttle and steering wheel - Manual, manual, Trim and trim method ● Anti-theft system - Remote lock code ● Charging / alternator - 12V-17A <p><u>Vanbrodski motor - 1 komad</u></p> <ul style="list-style-type: none"> ● Tip motora 4-taktni; ● Zapremina motora 747 cm3 ● Broj cilindara i raspored - Redni 3 cilindra ● Prečnik i hod - 65,0 mm X 75,0 mm ● Snaga motora - 29,4 KW/5.500 okretaja/min ● Maksimalni gas/ obrtaj motora - 6.000 okretaja/min ● Podmazivanje motora - Mokri karter ● Napajanje goriva - EFI ● Sistem paljenja - CDI ● Sistem pokretanja motora - Elektro start ● Prijenosni omjer - 2,0 (26/13) ● Osovina - S:414 mm L 563 mm ● Ukupna težina sa propelerom - 102 kg ● Kapacitet ulja - 1,7 litara ● Upravljačka komanda - Okretna ručka ● Gas i upravljač - Ručno ,ručno, Trim i metoda trima ● Sistem protiv krađe - Daljinski kod zaključavanja ● Punjenje /alternator - 12V-17A 			
19.	<p><u>Rafting boat for 8 people - 1 piece</u></p>			

<ul style="list-style-type: none"> ● <u>Material</u>: boat made of PVC material, bottom made of material (valmex or equivalent weight 1100 g / m) that is resistant to UV radiation, and boat tubes made of material (valmex weight 850 g / m) that is resistant to UV radiation, ● boat length minimum 425 cm and maximum 430 cm, ● the width of the boat must be a minimum of 200 cm and a maximum of 205 cm, ● The weight of the boat must be in the range of 45 kg - 65 kg ● the boat must have a blowing bottom on which there is an additional safety valve, ● the boat must consist of a minimum of 4 main chambers with valves, an inflatable bottom and a minimum of two transverse chambers ● the diameter of the main chambers must be at least 52 to 53 cm, ● There must be four supports on the boat called "D rings" which are used to hold the rope that runs the entire length ● the seating area must be reinforced with anti-slip material, the bottom must be at least 20 cm thick, the bottom must be glued to the boat ● stern and bow elevation from 25 cm to 27 cm at the bottom of the boat there must be leg holders for a maximum of 8 people, ● the boat should be complete with a transport bag and a boat repair kit, ● there must be two front and rear carrying handles on the boat, ● the boat must have water drainage holes of at least 35 mm, ● boats must be made in gray, yellow or red-blue color combination ● The boat must have a certificate of EN ISO 6185-1 <p><u>Rafting čamac za 8 osoba - 1 komad</u></p> <ul style="list-style-type: none"> ● <u>Materijal</u>: čamac od PVC materijal, dno izrađeno od materijala (valmex ili ekvivalent težine od 1100 g/m) koji je otporan na UV zračenje, a tube čamca izrađene od materijala (valmex težine 850 g/m) koji je otporan na UV zračenje, ● dužina čamca minimalno 425 cm i maksimalno 430 cm, ● širina čamca mora biti minimalno 200 cm i maksimalno 205 cm, ● težina čamca mora biti u rasponu od 45 kg – 65 kg ● čamac mora imati dno na duvanje na kojem se dodatno nalazi sigurnosni ventil, ● čamac se mora sastojati od minimalno 4 glavne komore sa ventilima, dno na naduvavanje i minimalno dvije poprečne komore ● prečnik glavnih komora mora biti minimalno 52 do 53 cm, 			
--	--	--	--

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
	<ul style="list-style-type: none"> ● na čamcu se moraju nalaziti četiri nosača pod nazivom „D prstenovi“ koji služe za držanje užeta koje se proteže čitavom dužinom ● zona sjedenja mora biti ojačana protukliznim materijalom, dno debljine minimalno 20 cm, dno mora biti zalijepljeno za čamac ● podignutost krme i pramca od 25 cm do 27 cm na dnu čamca moraju postojati držači za noge i to za maksimalno 8 ljudi, ● čamac treba da bude u kompletu sa transportnom torbom i setom za popravku čamaca, ● na čamcu se moraju nalaziti dvije ručke za nošenje naprije i nazad, ● na čamcu se moraju nalaziti rupe za ispuštanje vode koje su minimalno 35 mm, ● čamci moraju biti izrađeni u sivoj, žutoj ili crveno plavoj kombinaciji boja ● čamac mora posjedovati sertifikart o standardu EN ISO 6185-1. 			
20.	<p><u>Paddle - 16 pieces</u> handle - aluminum weight -820 g length 160 cm blade size - 768 cm² blade material - HDPE (High tough polyethylene) - high hardness polyethylene, resistant to temperatures -50 to +70 C, UV stable</p> <p><u>Veslo - 16 komada</u> ● drška – aluminij ● težina -820 g ● dužina 160 cm ● veličina lopatica – 768 cm² ● materijal lopatice – HDPE (High tough polyethylene) – polietilen visoke tvrdoće, otporan na temperature -50 do +70 C, UV stabilno</p>			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
21	<p><u>Boat trailer - 1 piece</u></p> <ul style="list-style-type: none"> ● Length: 5200 mm; ● width: 1550 mm; ● number of axles: 1; ● Load capacity: 520 kg; ● total weight: 750 kg; ● empty trailer weight: 230 kg; ● wheels: 4,5-10c ● Possibility of transporting boats up to 5 m and 520 kg. ● Shaft: torsion with waterproof ball bearings ● Nuts: stainless steel ● Equipment: 3 middle rollers, one height-adjustable roller ● 4 side rollers BRVG18 adjustable left-right-up-down shaft with waterproof hubs ● wheels 145R13, winch, electrical installation 12 V, front auxiliary wheel <p><u>Prikolica za čamce - 1 komad</u></p> <ul style="list-style-type: none"> ● Dužina: 5200 mm; ● širina: 1550 mm; ● broj osovine: 1; ● Nosivost: 520 kg; ● ukupna masa: 750 kg; ● težina prazne prikolice: 230 kg; ● točkovi: 4,5-10c ● Mogućnost prijevoza čamaca do 5 m i 520 kg. ● Osovina: torziona sa vodootpornim kugličnim ležajevima ● Matice: nehrđajući čelik od inox materijala ● Oprema: 3 srednja valjka, jedan valjak podesiv po visini ● 4 bočna rolera BRVG18 podesiva lijevo-desno-gore-dole ● osovina sa vodootpornim nabama ● točkovi 145R13, vitlo, električna instalacija 12 V, prednji pomoćni točak 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
22	<p><u>Car trailer - 1 piece</u></p> <ul style="list-style-type: none"> • ECO 2012 car trailer type • Box dimensions 201x126x110 cm • Total permissible weight 750 kg • Weight of empty car trailer 147 kg • Payload of the trailer 603 kg • Number of axles 1 • Tire size 155 / 70R13 • Galvanized sheet metal pages • Floor Waterproof wooden board • Opening the last page • Ore support wheel • 7-pin electrical connection type • Certificate D <p><u>Auto Prikolica za opremu - 1 komad</u></p> <ul style="list-style-type: none"> • Tip auto prikolice ECO 2012 • Dimenzije sanduka 201x126x110 cm • Ukupna dopuštena masa 750 kg • Težina prazne auto prikolice 147 kg • Korisna nosivost auto prikolice 603 kg • Broj osovine 1 • Dimenzija guma 155/70R13 • Stranice od pocinčanog lima • Pod Vodootporna drvena ploča • Otvaranje stranica Otvaranje zadnje stranice • Potporni kotačić na rudi • Vrsta električnog priključka 7 pinski • Atest D 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
23	<p><u>Static floating rope - 2 pcs</u></p> <ul style="list-style-type: none"> ● floating rope with SECURE technology ● Diameter (mm) 10.2 ● Length (m) 100 ● Weight (g / m) 60 ● Number of UIAA falls 20 ● Relative envelope mass (%) 47 ● Sheath slip (%) 0 ● Elongation (50 - 150 kg) (%) 2.6 ● Shrinkage (%) 0 ● Endurance (kN) 23 ● Min. endurance with knot (kN) 12 ● PA / PPV sheath / core material ● weight 55 Kg, drop factor 1 ● CE 1019 ● EN 1891 <p><u>Konopac statički plutajući - 2 kom</u></p> <ul style="list-style-type: none"> ● plutajući konop sa SECURE tehnologijom ● Promjer (mm) 10.2 ● Dužina (m) 100 ● Težina (g/m) 60 ● Broj UIAA padova 20 ● Relativna masa omotača (%) 47 ● Proklizavanje omotača (%) 0 ● Elongacija (50 - 150 kg) (%) 2.6 ● Skupljanje (%) 0 ● Izdržljivost (kN) 23 ● Min. izdržljivost sa čvorom (kN) 12 ● materijal PA / PPV plašt / jezgra ● težina 55 Kg, faktor pada 1 ● CE 1019 ● EN 1891 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
24	<p><u>Static rope - 2 pcs</u></p> <ul style="list-style-type: none"> ● Diameter (mm) 9 ● Length (m) 100 ● Weight (g / m) 59 ● Number of UIAA falls 16 ● Relative envelope mass (%) 44 ● Sheath slip (%) 0.2 ● Elongation (50 - 150 kg) (%) 3.6 ● Shrinkage (%) 1 ● Endurance (kN) 28 ● Min. endurance with knot (kN) 18 ● PA material ● Type A ● CE 1019 ● EN 1891 <p><u>Konopac statički - 2 kom</u></p> <ul style="list-style-type: none"> ● Promjer (mm) 9 ● Dužina (m) 100 ● Težina (g/m) 59 ● Broj UIAA padova 16 ● Relativna masa omotača (%) 44 ● Proklizavanje omotača (%) 0.2 ● Elongacija (50 - 150 kg) (%) 3.6 ● Skupljanje (%) 1 ● Izdržljivost (kN) 28 ● Min. izdržljivost sa čvorom (kN) 18 ● materijal PA ● Tip A ● CE 1019 ● EN 1891 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
25	<p><u>Oxygen resuscitation kit - 1 piece</u></p> <ul style="list-style-type: none"> • The kit is used to treat injured divers • 2.5-liter oxygen cylinder DIN 477 • The kit must contain <ul style="list-style-type: none"> · 100% oxygen by filling valve, · About 75% when using a rebreather mask · About 50% when oronasal is used · Resuscitation mask - Mandatory possibility of providing oxygen for 2 divers and has the possibility of connecting valves for additional demand, which allows the delivery of oxygen for 3 divers or for 2 divers only using the system "on request" - "On demand" valve <p><u>Komplet za reanimaciju kiseonikom- 1 komad</u></p> <ul style="list-style-type: none"> • Komplet služi za liječenje povrijeđenih ronioa • 2,5-litreni cilindar za kisik DIN 477 • Komplet mora sadržavati <ul style="list-style-type: none"> · 100% kiseonika pomoću ventila za punjenje, · oko 75% kada se koristi rebreather maska · oko 50% kada se koristi oronazalna · reanimacijsku masku. • Obavezna mogućnost pružanja kiseonika za 2 ronioca i ima mogućnost povezivanja ventila za dodatnu potražnju što omogućava isporuku kiseonika za 3 ronioca ili za 2 ronioca samo pomoću sistema "na zahtjev" • Ventil "na zahtjev" 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
26.	<p><u>Dry Suit - 10 pcs</u></p> <ul style="list-style-type: none"> • dry surface suit • four-layer AirFOUR material with breathable membrane or equivalent, Technical parameters of material WP25.000m / m, MVP15.000g / m2 / 24 HRS • Reinforcements on the knees, elbows and buttocks made of Cordura material or equivalent • diagonal front waterproof TI ZIP • latex cuffs around the neck and wrists • integrated Cordura socks or equivalent • adjustable belt that adjusts the suit to the user • extra neoprene on the neck • all seams are sewn and glued • reflective details • color: red <p><u>Spasilačko zaštitno odijelo - suho- 10 kom</u></p> <ul style="list-style-type: none"> • suho površinsko odijelo • četveroslojni AirFOUR materijal sa dišućom membranom ili ekvivalent, Tehnički parametri materijala WP25.000m / m, MVP15.000g / m2 / 24 HRS • pojačanja na koljenima, laktovima i stražnjici od materijala Cordura ili ekvivalent • dijagonalan prednji vodonepropusni TI ZIP • latex mandžeta oko vrata i zapešća • integrirane čarape od Cordure ili ekvivalent • podesivi pojas koji prilagođava odijelo korisniku • dodatni neopren na vratu • svi šavovi su šivani i lijepljeni • reflektirajući detalji • boja: crvena 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
27.	<p><u>Rescue boots - 10 pcs</u></p> <ul style="list-style-type: none"> ● Upper: impermeable material that includes efficient drainage from the inside and the possibility of closing the cuff of the built-in cap that eliminates the entry of small stones ● Purpose: canyoning ● Cartridge: Flexible ● Sole: non-slip ● Language adjustment loop ● Reflective elements ● Extended binding system ● Built-in cap <p><u>Gležnjericice- 10 kom</u></p> <ul style="list-style-type: none"> ● Gornji dio: nepropusni materijal koji uključuju učinkovito odvođenje vode iznutra i mogućnost zatvaranja manžete ugrađene kapice koja eliminiraju ulazak sitnih kamenčića ● Namjena: kanjon ● Uložak: Fleksibilan ● Potplata: protuklizna ● Petlja za podešavanje na jeziku ● Reflektirajući elementi ● Produženi sistem vezanja ● Ugrađena kapica 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
28.	<p><u>Undersuit for dry suit - 10 pcs</u></p> <ul style="list-style-type: none"> • Narrow suit with front zipper • Intended primarily as thermal insulation under a dry rescue suit • The coverall is made of "Tecnopile" material or equivalent • The material must be very light, elastic, breathable, quick-drying, wrinkle-free and wear-resistant <p>the sizes will be defined additionally</p> <p><u>Pododijelo za suho spailačko odijelo - 10 kom</u></p> <ul style="list-style-type: none"> • Odijelo uskog kroja s prednjim zatvaračem • Namijenjen prvenstveno kao toplinska izolacija ispod suhog odijela za spašavanje • Kombinezon je izrađen od "Tecnopile" materijala ili ekvivalent • Materijal mora biti vrlo lagan, elastičan, prozračan, brzo se sušiti, bez bora i otporan na habanje 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
29.	<p><u>Life jacket for rescuers- 10 pcs</u></p> <ul style="list-style-type: none"> ● Materials: CORDURA® 500D or equivalent, 100 nylon ● Dressing: Side buckle, front entrance ● Adjustment: Flex Fit <p>Security features:</p> <ul style="list-style-type: none"> ● Removable belt strap ● Test load of safety straps at 3.2 kN ● Reflective details <p>Pockets:</p> <ul style="list-style-type: none"> ● Large front pocket with divider and hanging positions ● Double-sided zipper compatible with radio antenna in front pocket ● Internal back pocket ● Certification: EN ISO 12402-5 / 12402-6 <p><u>Spasilački prsluk za spasioce - 10 kom</u></p> <ul style="list-style-type: none"> ● Materijali: CORDURA® 500D ili ekvivalent, 100% najlon ● Oblačenje: Bočna kopča, prednji ulaz ● Podešavanje: Flex Fit <p>Sigurnosne osobine:</p> <ul style="list-style-type: none"> ● Uklonjivi remen sa prstenom ● Ispitano opterećenje sigurnosnih naramenica na 3,2 kN ● Reflektujući detalji <p>Džepovi:</p> <ul style="list-style-type: none"> ● Veliki prednji džep sa razdjelnikom i pozicijama za kačenje ● Dvostrani patent zatvarač kompatibilan sa radio antenom na prednjem džepu ● Unutrašnji stražnji džep ● Sertifikacija: EN ISO 12402-5 / 12402-6 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
30.	<p><u>Safety rescue jacket for casualties - 10 pcs</u></p> <ul style="list-style-type: none"> ● Protective vest that has a large opening for the hands, which allows great freedom of movement. ● Material: 420 D nylon fabric / PE foam ● Has CE certificate ISO 12402-5. <p><u>Sigurnosi spasilački prsluk za unesrećene- 10 kom</u></p> <ul style="list-style-type: none"> ● Sigurnosni prsluk koji ima veliki otvor za ruke, čime je omogućena velika sloboda kretanja. ● Materijal: 420 D Nylon fabric / PE foam ● Posjeduje CE certifikat ISO 12402-5. 			
31.	<p><u>Umbilical cord - 10 pcs</u></p> <ul style="list-style-type: none"> ● tow rope in M and L sizes ● In the unstretched state, it has sizes M - 40 cm, L - 60 cm <p><u>Pupčana vrpca - 10 kom</u></p> <ul style="list-style-type: none"> ● uža za vuču u kompletu M i L veličina ● U nenapregnutom stanju ima veličine M – 40 cm, L – 60 cm 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
32.	<p><u>Rescue rope in a bag - 10 pcs</u></p> <ul style="list-style-type: none"> ● weight: 1436 g / length: 25 m ● Bag made of CORDURA® 500 D or equivalent with built-in foam flotation ● durability: 10 kN static breaking strength ● rope: 25 m high visibility rope, floating, 11 mm polypropylene core rope ● other features: ● The rope can be detached and used independently ● Close the bag ● Extra fabric on the opening to help with throwing and repacking ● Reflective details ● Clean line attachment point ● Compatible quick release strap <p><u>Spasilačko uže u torbi - 10 kom</u></p> <ul style="list-style-type: none"> ● težina: 1436 g / dužina: 25 m ● Vrećica izrađena CORDURA® 500 D ili ekvivalent sa ugrađenom pjenastom flotacijom ● izdržljivost: 10 kN statička prekidna čvrstoća ● uže: 25 m uže visoke vidljivosti, plutajuće, uže u jezgri od polipropilena od 11 mm ● ostale karakteristike: ● Uže se može izdvojiti i koristiti samostalno ● Zatvaranje vrećice ● Dodatna tkanina na otvoru za pomoć u bacanju i prepakiranju ● Reflektirajući detalji ● Tačka pričvršćenja čiste linije ● Kompatibilni remen za brzo otpuštanje 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
33	<p><u>Belt for a bag with a rope - 10 pcs</u></p> <ul style="list-style-type: none"> ● Waist belt, or as a quick release leash attached to an SUP. With two quick-release buckles, with reinforced strap for fastening. <p><u>Pojas za torbu sa užetom - 10 kom</u></p> <ul style="list-style-type: none"> ● Pojasni remen za nošenje oko struka, ili kao quick release leash pričvršćen za SUP. Sa dvije kopče za brzo otpuštanje, sa pojačanim remenom za pričvršćivanje. 			
34	<p><u>Safety helmet - 10 pcs</u></p> <ul style="list-style-type: none"> ● Protective helmet with ear protection ● thermoplastic shell ● Protection against side impacts ● Ventilation openings ● Adjustable side release buckle ● Internal adjustable bracket ● EN 1385 <p><u>Zaštitna kaciga - 10 kom</u></p> <ul style="list-style-type: none"> ● Zaštitna kaciga sa zaštitom oko ušiju ● termoplastična školjka ● Zaštita od bočnih udara ● Ventilacijski otvori ● Podesiva kopča za bočno oslobađanje ● Unutarnji podesivi nosač ● EN 1385 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
35	<p><u>Lifeguard gloves - 10 pairs</u> Gloves for rescue teams, adapted for work in difficult weather conditions. Materials: 2 mm Titanium neoprene, Armortex neoprene or equivalent Color: red</p> <p><u>Rukavice za spasioce - 10 pari</u></p> <ul style="list-style-type: none"> • Rukavice za spasilačke ekipe, prilagođene za rad u teškim vremenskim uslovima. • Materijali: 2 mm Titanium neopren, Armortex neopren ili ekvivalent • Boja: crvena 			
36	<p><u>Knife - 10 pcs</u></p> <ul style="list-style-type: none"> • Blade length: 135 mm • Blade material: 1.4110 steel (HRC 56, stainless) • Overall length: 270 mm • Glass-fiber-reinforced non-slip handle • Window breaker • Nylon holster for fastening to PA strap or belt • holster <p><u>Nož - 10 kom</u></p> <ul style="list-style-type: none"> • Duljina oštrice: 135 mm • Materijal oštrice: 1,4110 čelik (HRC 56, nehrđajući) • Ukupna duljina: 270 mm • Neklizajuća ručka ojačana staklenim vlaknima • Razbijač prozora • Najlonska futrola za pričvršćivanje na PA remen ili remen • futrola 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
37	<u>Whistle - 10 pcs</u> <ul style="list-style-type: none"> • Three-chamber whistle design - produces up to 110 decibels. • Color: red <u>Zviždaljka - 10 kom</u> <ul style="list-style-type: none"> • Trokomorni dizajn zviždaljke - proizvodi do 110 decibela. • Boja: crvena 			
38	<u>Impenetrable bag - 5 pcs</u> <ul style="list-style-type: none"> • General purpose bag and is wear resistant and very durable. • 100% dry 10 L bag • Highly durable fabric with PVC coating. • Height: 80cm • Width: 49.5 cm • Weight: 50g <u>Nepromoćiva torba - 5 kom</u> <ul style="list-style-type: none"> • vreća opšte namjene i otporna je na habanje i vrlo izdržljiva. • 100% suha vreća od 10 L • visoko izdržljiva tkanina s PVC premazom. • Visina: 80cm • Širina: 49,5cm • Težina: 50g 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
39	<p><u>Two-part ABS stretcher - 2 pcs</u></p> <ul style="list-style-type: none"> • Dimensions: 2200 x 650 x 200 mm • Weight: 17 kg • Shelf life: 12 years • Load capacity: 315 kg (1 person) • CERTIFICATES: EN 1865 <p><u>Dvodjelna ABS nosila - 2 kom</u></p> <ul style="list-style-type: none"> • Dimenzije: 2200 x 650 x 200 mm • Težina: 17 kg • Vijek trajanja: 12 godina • Nosivost: 315 kg (1 osoba) • CERTIFIKATI: EN 1865 			
40	<p><u>Transport rescue stretcher - 1 pcs</u></p> <ul style="list-style-type: none"> • Maximum load: 160kg • Length without frame (single) / weight: 94 cm, with frame 104 cm, • Lifebuoy length / weight: 200 cm, 8kg • Width: 44 cm • Single wheel, 4 kg • Handles for transporting lifebuoys using a wheel • The stretcher also includes handles for transporting the stretcher for the wheel and the wheel for transporting the stretcher <p><u>Transporta nosila za spasavanje - 1 kom</u></p> <ul style="list-style-type: none"> • Maksimalna nosivost: 160kg • Dužina bez okvira (pojedinačno)/težina: 94 cm, sa okvirom 104 cm, • Dužina nosila za spasavanje/težina: 200 cm, 8kg • Širina: 44 cm • Jednostruki točak, 4 kg • Ručke za transport spasilačkih nosila koja koriste točak • Nosila uključuju i ručke za transport nosila za točak i točak za transport nosila 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
41	<p><u>Pick Up stretcher and head restraint (set) - 1 pcs</u></p> <ul style="list-style-type: none"> ● The stretcher includes three fixation straps with a quick release buckle and a head restraint ● Shortened length 1660 mm ● Intermediate length 1 1780 mm ● Intermediate length 2 1900 mm ● Intermediate length 3 2050 mm ● Folded length 1190 mm ● Thickness folded 70 mm ● Thickness opened 65 mm ● Width 440 mm ● Material Aluminum ● Loading capacity 170 kg ● Weight $7,9 \pm 0,4$ kg ● UNI EN 1865-1 <p><u>Pick Up nosila i fiksator za glavu (komplet) - 1 kom</u></p> <ul style="list-style-type: none"> ● Nosila uključuju tri fiksacijske trake sa kopčom za brzo otpuštanje i fiksator za glavu ● Skraćena dužina 1660 mm ● Srednja dužina 1 1780 mm ● Srednja dužina 2 1900 mm ● Srednja dužina 3 2050 mm ● Dužina sklopljene 1190 mm ● Debljina presavijenog 70 mm ● Debljina otvora 65 mm ● Širina 440 mm ● Materijal aluminijum ● Nosivost 170 kg ● Težina $7,9 \pm 0,4$ kg ● UNI EN 1865-1 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
42	<p><u>Immobilization board - 2 pcs</u></p> <ul style="list-style-type: none"> ● Board including straps with release buckle, Basic part with 2 side headrests, as well as a ring for fixing the forehead and chin ● Load capacity: 250 kg ● Dimensions: 1880 x 440 x 70 mm ● Weight: approx. 6.3 kg ● X-ray permeable, MR and CT compatible <p><u>Daska za imobilizaciju - 2 kom</u></p> <ul style="list-style-type: none"> ● Daska koja uključuje i trake sa kopčom na otpuštanje, Osnovni dio s 2 bočna naslona za glavu, kao i prsten za učvršćivanje čela i brade ● Nosivost: 250 kg ● Dimenzije: 1880 x 440 x 70 mm ● Težina: oko 6,3 kg ● RTG propusna, MR i CT kompatibilna 			
43	<p><u>Head fasteners - 2 pcs</u></p> <ul style="list-style-type: none"> ● Contents: Basic part with 2 side headrests, as well as a ring for fixing the forehead and chin. ● Dimensions: 250-400-175mm ● Weight: 900 gr <p>compatible with immobilization board(Uređeno)Vrati izvorni tekst</p> <p><u>Fiksatori za glavu - 2 kom</u></p> <ul style="list-style-type: none"> ● Sadržaj: Osnovni dio s 2 bočna naslona za glavu, kao i prsten za učvršćivanje čela i brade. ● Dimenzije: 250-400-175mm ● Težina : 900 gr <p>kompatibilni sa daskom za imobilizaciju</p>			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
44	<p><u>Mobile GPS navigation - 12 pcs</u></p> <ul style="list-style-type: none"> ● DIMENSIONS 2.1 "x 4.0" x 1.3 "(5.4 x 10.3 x 3.3 cm) ● SCREEN SIZE 1.4 "x 1.7" (3.5 x 4.4 cm); 2.2 "diameter (5.6 cm) ● SCREEN RESOLUTION 240 x 320 pixels ● TYPE SCREEN 2.2 "transflective, 65K color TFT ● WEIGHT 5 oz (141.7 g) with batteries ● BATTERIES TYPE 2 AA batteries (not included); NiMH or lithium is recommended ● BATTERY LIFE 25 hours ● WATERPROOF IPX7 ● mini USB interface ● MEMORY / HISTORY 8 GB <p><u>Mobilna GPS navigacija - 12 kom</u></p> <ul style="list-style-type: none"> ● DIMENZIJE 2,1" x 4,0" x 1,3" (5,4 x 10,3 x 3,3 cm) ● VELIČINA ZASLONA 1,4" x 1,7" (3,5 x 4,4 cm); promjer 2,2" (5,6 cm) ● REZOLUCIJA ZASLONA 240 x 320 piksela ● TIP ZASLON 2,2" transflektivni, 65K boja TFT ● TEŽINA 5 oz (141,7 g) s baterijama ● BATERIJE TIP 2 AA baterije (nisu uključene); Preporučuje se NiMH ili litij ● VIJEK BATERIJE 25 sati ● VODOOTPORNA IPX7 ● SUČELJE mini USB ● MEMORIJA/POVIJEST 8 GB 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
45	<p><u>Power bank for phones - 5 pcs</u></p> <ul style="list-style-type: none"> ● Cable length: 60 cm ● Battery capacity: 20000 mAh ● Battery type: lithium polymer ● Input: USB 3.0 ● Charging power: 20 W ● To charge three devices at the same time ● Power key ● 1x USB-C to USB-C charging cable <p><u>Power bank za telefone - 5 kom</u></p> <ul style="list-style-type: none"> ● Duljina kabela: 60 cm ● Kapacitet baterije: 20000 mAh ● Tip baterije: litij-polimerna ● Ulaz: USB 3.0 ● Snaga punjenja: 20 W ● Za istovremeno punjenje tri uređaja ● Tipka za uključivanje / isključivanje ● 1x USB-C v USB-C kabel za punjenje 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
46	<p><u>Set - Handheld mobile station, with single charger, battery, antenna, spare battery and spare antenna - 8 pcs</u></p> <ul style="list-style-type: none"> • Channel distance (kHz) - 12.5; 25; 20; 12.5 (6.25 effective) • VHF frequency range (136-174 MHz); UHF (403-470 MHz) • Channel number 16 • Battery life (based on duty cycle 05 05 90) • NiMH (1400 mAh) analog battery: 9 hours Digital: 11.5 hours • Dimensions H x W x D (with standard battery) • 127.7 X 61.5 X 42.0 mm (NiMH 1400 mAH) • Weight (with standard battery) 406 g (NiMH 1400 mAH) • Mil spec 810 C; 810 D; 810 E; 810 F; 810 G • IP standards IP54 <p><u>Komplet – Ručna mobilna stanica, sa jedinačnim punjačem, baterijom, antenom, rezervnom baterijom i rezervnom antenom - 8 kom</u></p> <ul style="list-style-type: none"> • Razmak kanala (kHz) - 12,5; 25; 20; 12,5 (6,25 učinkovito) • Frekvencijski raspon VHF (136-174 MHz); UHF (403-470 MHz) • Broj kanala 16 • Trajanje baterije (na temelju radnog ciklusa 05 05 90) • NiMH (1400 mAh) analogna baterija: 9 sati Digitalna: 11,5 sati • Dimenzije V x Š x D (sa standardnom baterijom) • 127,7 X 61,5 X 42,0 mm (NiMH 1400 mAH) • Težina (sa standardnom baterijom) 406 g (NiMH 1400 mAH) • Mil spec 810 C; 810 D; 810 E; 810 F; 810 G • IP standardi IP54 			
47	<p><u>Group charger 6 outlets - 1 pc</u> MUC for charging six units with battery connected. With EU-plus (230V)</p> <p><u>Grupni punjač 6 utičnica- 1 kom</u> MUC za punjenje šest jedinica s priključenom baterijom. S EU-plus (230V)</p>			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
48	<p><u>Car radio for vehicles with appropriate magnetic antenna - 1 pc</u></p> <ul style="list-style-type: none"> ● Portable station, for vehicle, with microphone, vehicle mount bracket and power cord ● Mobile transceiver ● Analog / Digital ● VHF 136 to 174MHz ● Includes microphone + power cord ● VHF ● Frequency range: 403 - 470 MHz ● Channel separation: > 12.5 kHz - 20 kHz - 25 kHz ● Channels: 16 channels ● Power: 1 W / 25 W ● Sensitivity (12dB SINAD): 0.22 μV ● Switches and buttons: Panic button <p><u>Kolska radio stanica za vozila s odgovarajućom magnetnom antenom - 1 kom</u></p> <ul style="list-style-type: none"> ● Prijenosna stanica, za vozilo, sa mikrofonom, nosačem za montažu u vozilo i napojnim kabelom ● Mobilni primopredajnik ● Analogno/Digitalno ● VHF 136 do 174MHz ● Uključuje mikrofoni + kabel za napajanje ● VHF ● Frekvencijski raspon: 403 – 470 MHz ● Razdvajanje kanala: > 12,5 kHz – 20 kHz – 25 kHz ● Kanali: 16 kanala ● Snaga: 1 W/25 W ● Osjetljivost (12dB SINAD): 0,22 μV ● Prekidači i tipke: Panik tipka 			

49	<p><u>Portable repeater with original antenna - 1 pc</u></p> <p>Frequency range VHF - 136-174 MHz and UHF -400-527 MHz</p> <ul style="list-style-type: none"> ● Channel spacing 12.5 / 20/25 kHz ● Frequency stability 0.5 ppm ● Frequency Generation Synthesized ● Channel capacity 64 ● RF output power 1-10 W ● Dimensions * (H x W x D) 279 x 229 x 102 mm (11 x 9 x 4 in) ● Weight * 4.54 kg (10 lbs) ● Input voltage (DC) 12 V (11.0-15.5 V) ● Current (standby) 0.7 A (0.63 A typical) ● Current (transmission at 10 W) 3A (typical) ● Input power modes DC only, optional AC / DC ● Operating temperature - Range -30 to +60 ° C (-22 to +140 ° F) ● IP65 input rating ● Maximum duty cycle 100% ● Digital vocoder type AMBE + 2 TM or equivalent ● Connectivity, left side Rx (N female) ● Connectivity, right side Tx (N female) ● Connectivity, lower USB B socket, 1x Ethernet, ● RJ45 accessory connector, DC input ● Half Duplex / Duplex modes ● Supported system - Digital conventional, IP Site Connect or equivalent <p>Capacity ● Plus, Max Capacity, Connect Plus.</p> <ul style="list-style-type: none"> ● Analog conventional, digital voting, MPT 1327. ● Sound levels - Input: Unbalanced: Adjustable, 80 mV rms nominally by 60% RSD. Output: Unbalanced: Adjustable, 330 mV rms nominal @ 60% RSD. ● FCC emissions - labels - 11K0F3E, 16K0F3E, 7K60FXD, 7K60F7D, 7K60FXE, 7K60F7E, 7K60F7W, 7K60FXW ● Acceptance of FCC type VHF - ABZ99FT3096 and UHF - ABZ99FT4100 ● IC description VHF - 109AB-99FT3096 and UHF - 109AB-99FT4100 <p>RECEIVER</p> <p>Frequency range VHF - 136-174 MHz UHF - 400-527 MHz</p> <p>Sensitivity, 12dB SINAD 0.3 uV (0.22 uV typical)</p> <p>Sensitivity, 5% BER 0.25 uV (0.18 uV typical)</p>			
----	--	--	--	--

<p>Selectivity (TIA603D), VHF - 12.5 / 20/25 kHz 55/83/83 dB UHF - 55/80/80 dB</p> <p>Selectivity (TIA603), VHF - 12.5 / 20/25 kHz 68/83/83 UHF - dB 68/80/80 dB</p> <p>Intermodulation rejection (TIA603D / ETSI) 80/70 Db (82/73 dB typical)</p> <p>False rejection (TIA603D / ETSI) 85/75 dB (typical 95/90 dB)</p> <p>Sound distortion <3% (<1% typical)</p> <p>Noise and noise, 12.5 / 20/25 kHz -45 / -50 / -50 dB</p> <p>Blocking -57 dBm</p> <p>TRANSMITTER</p> <p>Frequency range VHF - 136-174 MHz UHF - 400-527 MHz</p> <p>RF output power 1-10 W</p> <p>Maximum duty cycle 100%</p> <p>Intermodulation attenuation 40 dB</p> <p>Adjacent Channel Power (TIA603D), 12.5 / 20/25 kHz 62/78/78 dB</p> <p>Implemented false emissions -36 dBm <1 GHz, -30 dBm> 1 GHz</p> <p>Audio response TIA603D / ETSI</p> <p>Sound distortion <1%</p> <ul style="list-style-type: none"> • ETSI 300-086 • ETSI 300-113 • TIA603D • CE mark • RoHS2 compliant • On the UL list • Digital protocol ESTI TS 102 361-1, -2, -3 (DMR Tier II and III) <p><u>Prenosni repetitor sa originalnom antenom - 1 kom</u></p> <p>Frekvencijski raspon VHF - 136-174 MHz i UHF -400-527 MHz</p> <ul style="list-style-type: none"> • Razmak kanala 12,5 / 20 / 25 kHz • Stabilnost frekvencije 0,5 ppm • Generiranje frekvencije Sintetizirano • Kapacitet kanala 64 • RF izlazna snaga 1-10 W • Dimenzije* (V x Š x D) 279 x 229 x 102 mm (11 x 9 x 4 in) • Težina 4,54 kg (10 lbs) • Ulazni napon (DC) 12 V (11,0-15,5 V) • Struja (pripravnost) 0,7 A (0,63 A tipično) • Struja (prijenos pri 10 W) 3A (tipično) • Načini ulaznog napajanja Samo DC, izborna AC/DC • Radna temperatura - Raspon -30 do +60 °C (-22 do +140 °F) 			
--	--	--	--

<ul style="list-style-type: none"> ● Ulazna ocjena IP65 ● Maksimalni radni ciklus 100% ● Digitalni vokoder tipa AMBE+2™ ili ekvivalent ● Povezivost, lijeva strana Rx (N ženski) ● Povezivost, desna strana Tx (N ženski) ● Povezivost, donji USB B utičnica, 1x Ethernet, ● RJ45 konektor za dodatnu opremu, DC ulaz ● Načini rada Half Duplex / Duplex ● Podržani sustav - Digitalni konvencionalni, IP Site Connect ili ekvivalent <p>Kapacitet ● Plus, Max Capacity, Connect Plus.</p> <ul style="list-style-type: none"> ● Analogno konvencionalno, digitalno glasanje, MPT 1327. ● Razine zvuka - Ulaz: Neuravnotežen: Podesiv, 80 mV rms nominalno za 60% RSD. Izlaz: Neuravnotežen: Podesiv, 330 mV rms nominalno @ 60% RSD. ● FCC emisija – oznake - 11K0F3E, 16K0F3E, 7K60FXD, 7K60F7D, 7K60FXE, 7K60F7E, 7K60F7W, 7K60FXW ● Prihvatanje FCC tipa VHF - ABZ99FT3096 i UHF - ABZ99FT4100 ● Opis IC-a VHF - 109AB-99FT3096 i UHF - 109AB-99FT4100 <p>PRIJAMNIK</p> <p>Frekvencijski raspon VHF - 136-174 MHz UHF - 400-527 MHz</p> <p>Osjetljivost, 12dB SINAD 0,3 uV (0,22 uV tipično)</p> <p>Osjetljivost, 5% BER 0,25 uV (0,18 uV tipično)</p> <p>Selektivnost (TIA603D), VHF - 12,5 / 20 / 25 kHz 55 / 83 / 83 dB</p> <p>UHF - 55 / 80 / 80 dB</p> <p>Selektivnost (TIA603), VHF - 12,5 / 20 / 25 kHz 68 / 83 / 83 UHF - dB 68 / 80 / 80 dB</p> <p>Odbijanje intermodulacije (TIA603D/ETSI) 80 / 70 Db (82 / 73 dB tipično)</p> <p>Lažno odbijanje (TIA603D/ETSI) 85 / 75 dB (tipično 95 / 90 dB)</p> <p>Izobličenje zvuka < 3% (<1% tipično)</p> <p>Šum i šum, 12,5 / 20 / 25 kHz -45 / -50 / -50 dB</p> <p>Blokiranje -57 dBm</p> <p>ODAŠILJAČ</p> <p>Frekvencijski raspon VHF - 136-174 MHz UHF - 400-527 MHz</p> <p>RF izlazna snaga 1-10 W</p> <p>Maksimalni radni ciklus 100%</p> <p>Intermodulacijska slabljenja 40 dB</p>			
---	--	--	--

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
	<p>Snaga susjednog kanala (TIA603D), 12,5 / 20 / 25 kHz 62 / 78 / 78 dB</p> <p>Provedene lažne emisije -36 dBm < 1 GHz, -30 dBm > 1 GHz</p> <p>Audio odgovor TIA603D / ETSI</p> <p>Izobličenje zvuka <1%</p> <ul style="list-style-type: none"> ● ETSI 300-086 ● ETSI 300-113 ● TIA603D ● Oznaka CE ● Sukladno RoHS2 ● Na listi UL ● Digitalni protokol ESTI TS 102 361-1, -2, -3 (DMR Tier II i III) 			

50	<p><u>Antenna - 1 pc</u> Stacking 23cm 7 x 5/8 λ</p> <ul style="list-style-type: none"> • Supported straps 2m 70cm 23cm • Weight (transport) [kg] 1 • Gain 1296 MHz [dBi] 11.7 • Amplification 432 MHz [dBi] 8.3 • Amplification 144 MHz [dBi] 4.5 • Impedance 50 • Stacking 70cm 3 x 5/8 λ • Mono- / Multiband Tri band • Stacking 2m 6/8 λ • Max. Power [W] 100 W • Frequency range 144-146, 430-440, 1240-1300 MHz • Vertical polarization • VHF / UHF Omni antenna design • Max. Mast diameter [mm] 30 - 62 mm • N-Buchse connection • Weight [kg] 1.00 kg <p><u>Antena - 1 kom</u> Slaganje 23cm 7 x 5/8 λ</p> <ul style="list-style-type: none"> • Podržane trake 2m 70cm 23cm • Težina (prijevoz) [kg] 1 • Pojačanje 1296 MHz [dBi] 11.7 • Pojačanje 432 MHz [dBi] 8.3 • Pojačanje 144 MHz [dBi] 4.5 • Impedancija 50 • Slaganje 70cm 3 x 5/8 λ • Mono-/Multiband Tri band • Slaganje 2m 6/8 λ • Maks. Snaga [W] 100 W • Frekvencijski raspon 144-146, 430-440, 1240-1300 MHz • Vertikalna polarizacija • Dizajn antene VHF/UHF Omni • Maks. Promjer jarbola [mm] 30 - 62 mm • Priključak N-Buchse • Težina [kg] 1,00 kg 			
----	---	--	--	--

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
51	<p><u>Power supply unit - 1 pc</u></p> <ul style="list-style-type: none"> ● Wave (mV) <80 mVpp at nominal value ● Output voltage (V) 13.8V + 9-15V ● Max. Current output (A) 28 ● Max. Continuous current output (A) 20 ● Fuses 5A ● Current [A] 28 ● Voltage display Yes. analog ● Protection measures Kurzschlußfest, Strombegrenzung 28A ● Size W x H x D 155 x 70 x 205 mm ● Weight [kg] 1.50 kg <p><u>Napojna jedinica - 1 kom</u></p> <ul style="list-style-type: none"> ● Talasanje (mV) < 80 mVpp pri nominalnoj vrijednosti ● Izlazni napon (V) 13,8V + 9-15V ● Maks. Strujni izlaz (A) 28 ● Maks. Kontinuirani strujni izlaz (A) 20 ● Osigurači 5A ● Struja [A] 28 ● Prikaz napona Da. analogni ● Mjere zaštite Kurzschlußfest, Strombegrenzung 28A ● Veličina Š x V x D 155 x 70 x 205 mm ● Težina [kg] 1,50 kg 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
52	<p><u>Gas toop heater - 2 pcs</u></p> <ul style="list-style-type: none"> ● Voltage 230 V / 50 Hz ● Heating power 30 kW ● Air flow 650 m3 / h ● Heating space 300 - 600 m2 ● Fuel consumption 2.18 kg / h ● Dimensions 475 x 225 x 360 mm ● Weight 6.1 kg ● Pipe and regulator included <p><u>Plinska toop grijalica – 2 kom</u></p> <ul style="list-style-type: none"> ● Napon 230 V / 50 Hz ● Snaga grijanja 30 kW ● Protok zraka 650 m3/h ● Prostor zagrijavanja 300 - 600 m2 ● Potrošnja goriva 2.18 kg/h ● Dimenzije 475 x 225 x 360 mm ● Težina 6.1 kg ● Uključena cijev i regulator 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
53	<p><u>Laptop - 3 pcs</u></p> <ul style="list-style-type: none"> ● Processor: 6 Core, 16MB up to 4.2 GHz, ● RAM 16GB DDR4-3200, ● screen 15.6 "FullHD WVA 120Hz 3ms 1920x1080 250nits Anti-Glare, 512GB PCIe NVMe SSD, ● Windows 10 Pro or equivalent, ● NVIDIA GeForce RTX 3050 4GB graphics card or equivalent, HD webcam, ● stereo speakers, Killer Wi-Fi 6 AX1650 (2x2) or equivalent ● Bluetooth, 3x USB 3.2.1x USB 3.2 Type-C, HDMI, ● weight max 2.60 kg ● Laptop bag <p><u>Laptop - 3 kom</u></p> <ul style="list-style-type: none"> ● Procesor: 6 Core, 16MB up to 4.2 GHz, ● RAM 16GB DDR4-3200, ● ekran 15,6" FullHD WVA 120Hz 3ms 1920x1080 250nits Anti-Glare, 512GB PCIe NVMe SSD, ● operativni sistem Windows 10 Pro ili ekvivalent, ● grafička kartica NVIDIA GeForce RTX 3050 4GB ili ekvivalent, ● HD web kamera, ● stereo zvučnici, Killer Wi-Fi 6 AX1650 (2x2) ili ekvivalent ● Bluetooth, 3x USB 3.2,1x USB 3.2 Type-C, HDMI, ● težina max 2,60 kg ● Torba za laptop 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
54	<p><u>Gasoline generator - 1 pc</u></p> <ul style="list-style-type: none"> ● Voltage: 230 V - single phase ● Power: minimum 5 kW ● Max. power: 5.5 kW ● Engine: GX390 4-stroke or equivalent, air-cooled engine ● Noise level: 82 dBA ● Fuel tank capacity: 24 l ● Nominal operating time approx. 8:10 h, ● Sockets: 2x shock ● Dimensions: 68.1 x 53 x 57.1 cm ● Weight: 82.5 kg <p><u>Agregat benzinski - 1 kom</u></p> <ul style="list-style-type: none"> ● Napon: 230 V – monofazni ● Snaga: minimalno 5 kW ● Maks. snaga: 5.5 kW ● Motor: GX390 4-taktni ili ekvivalent, zrakom hlađeni motor ● Razina buke: 82 dBA ● Zapremina spremnika goriva: 24 l ● Nazivno vrijeme rada cca 8:10 h, ● Utičnice: 2x šuko ● Dimenzije: 68,1 x 53 x 57,1 cm ● Težina: 82,5 kg 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
55	<p><u>Machete - 5 pcs</u></p> <ul style="list-style-type: none"> ● Universal machete ● Length: 505 mm ● Weight: 450 g ● Material: blade special carbon steel, handle FibreComp material or equivalent resistant to all weather conditions. Plastic ax and machete housing that includes a safety lock that opens and closes easily and features a comfortable carrying and hanging handle <p><u>Mačeta - 5 kom</u></p> <ul style="list-style-type: none"> ● Univerzalna mačeta ● Dužina: 505 mm ● Težina: 450 g ● Materijal: oštrica posebni ugljični čelik, drška FibreComp materijala ili ekvivalent otporna na sve vremenske uvjete. Plastično kućište za sjekiru i mačetu koje uključuje namješteno sigurnosno zaključavanje, a koje se jednostavno otvara i zatvara i sadrži udobnu ručku za nošenje i vješanje 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
56	<p><u>Inflatable base tent - 1 pc</u></p> <ul style="list-style-type: none"> ● Material: Pneumatic frame arches made of composite PVC and Hypalon neoprene material, Sheath made of Teflon-coated polyester fabric on both sides or equivalent. ● Floor combined with tent walls. ● The material of the tent must guarantee the use of the tent in the temperature range from -40°C to + 70°C. ● width: 7.5 m / length 11.6 m / height 3.5 m ● area: 87 m² ● door dimensions: 2.5 x 2.8 m ● number of windows 8 ● pneumatic arches: Ø 40cm ● number of valves: 2 ordinary and 1 safety on each arch <p><u>Bazni šator na napuhavanje - 1 kom</u></p> <ul style="list-style-type: none"> ● Materijal: Pneumatske arke rama od kompozitnog PVC i Hypalon neopren materijala, Plašt napravljen od poliesterske tkanine obložene Teflonom sa obe strane ili ekivalent. ● Pod kombinovan sa zidovima šatora. ● Materijal šatora mora garantovati korištenje šatora u rasponu temperatura od -40°C do + 70°C. ● širina: 7.5 m / dužina 11.6 m / visina 3.5 m ● površina: 87 m² ● dimenzije vrata: 2.5 x 2.8 m ● broj prozora 8 ● pneumatske arke: Ø 40cm ● broj ventila: 2 obična i 1 sigurnosni na svakoj arci 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
57	<p><u>Folding table - 4 pcs</u></p> <ul style="list-style-type: none"> ● Folding table, white color, dimensions 180x76x74 cm Iron construction, pipe diameter 25 mm. ● Material: 4 cm thick plastic ● Transport dimensions: 76.5x8.5x92 cm ● Weight: 12.5 / 13.5 kg <p><u>Sklopivi stol - 4 kom</u></p> <ul style="list-style-type: none"> ● Sklopivi stol, dimenzije 180x76x74 cm Željezna konstrukcija, promjer cijevi 25 mm. ● Materijal: plastika debljine 4 cm ● Transportne dimenzije: 76.5x8.5x92 cm ● Težina :12.5/13.5 kg 			
58	<p><u>Folding plastic chairs - 20 pcs</u></p> <ul style="list-style-type: none"> ● Seat width: 450 mm ● Seat depth: 430 mm ● Seat height: 490 mm ● Total height: 850 mm ● Folded height: 1070 mm ● Seat material: Plastic ● Stand material: Steel ● Load capacity: 110 kg ● Weight: 3.85 kg <p><u>Sklopive plastične stolice - 20 kom</u></p> <ul style="list-style-type: none"> ● Širina sjedala:450 mm ● Dubina sjedala:430 mm ● Visina sjedišta:490 mm ● Ukupna visina:850 mm ● Visina sklopljenog:1070 mm ● Materijal sjedišta:Plastika ● Materijal postolja:Čelik ● Nosivost:110 kg ● Težina:3,85 kg 			

59	<p><u>Personal first aid refill - 5 sets</u></p> <p><u>1 set contains:</u></p> <ul style="list-style-type: none"> ● Contents of one charge - specification of contents for 1 set ● Triangular scarf 100x100x140cm - 5pcs, ● Compress 10cm x 10cm... 5pcs, ● Absorbent gauze 0.4 m2... 1pc, ● Absorbent gauze 0.8 m2... 1pc, ● Aluplast compress 9cm x 5cm... 10pcs, ● Calico 6cm x 4m... 5pcs, ● Calico 8cm x 5m... 5pcs, ● Calico 10cm x 4m... 5pcs, ● Calico 10cm x 5m... 2pcs, ● Compress 8cm x 3m... 5pcs, ● Compress 10cm x 4m... 2pcs, ● Compress 5cm x 5cm... 5pcs, ● Aluplast 50cm x 60cm... 1pc, ● Disposable gloves... 10pcs, ● Plaster 10cm x 4cm... 5pcs, ● Plaster 10cm x 8cm... 5pcs, ● Plaster 2cm x 1cm... 1pc, ● Plaster 2cm x 5cm... 1pc, ● Scissors with rounded tip... 1pc, ● Ziherica... 5pcs, ● Sanitary wool 100g... 1pc, ● First bandage - sterile gauze - 5 pieces ● Mandatory with the filling of a suitcase / bag or backpack in which the filling will be <p><u>Punjenje za ličnu prvu pomoć - 5 setova</u></p> <p><u>1 set sadrži:</u></p> <p>Sadržaj jednog punjenja - specifikacija sadržaja za 1 komplet</p> <ul style="list-style-type: none"> ● Trokutasta marama 100x100x140cm - 5kom, ● Kompresa 10cm x 10cm ...5kom, ● Upojna gaza 0,4 m2...1kom, ● Upojna gaza 0,8 m2...1kom, ● Aluplast kompresa 9cm x 5cm ...10kom, ● Kaliko 6cm x 4m...5kom, ● Kaliko 8cm x 5m...5kom, ● Kaliko 10cm x 4m...5kom, ● Kaliko 10cm x 5m...2kom, ● Kompresa 8cm x 3m...5kom, 			
----	---	--	--	--

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
	<ul style="list-style-type: none"> ● Kompresa 10cm x 4m...2kom, ● Kompresa 5cm x 5cm...5kom, ● Aluplast 50cm x 60cm...1kom, ● Rukavice za jednokratnu uporabu...10kom, ● Flaster 10cm x 4cm...5kom, ● Flaster 10cm x 8cm...5kom, ● Flaster 2cm x 1cm...1kom, ● Flaster 2cm x 5cm...1kom, ● Škare sa zaobljenim vrhom...1kom, ● Zihherica...5kom, ● Sanitarna vata 100g...1kom, ● Prvi zavoj - sterilna gaza - 5 komada ● Obavezno uz punjenje kofer/torba ili ruksak u kome će biti punjenje 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
60	<p><u>Alpine belt - 5 pcs</u></p> <ul style="list-style-type: none"> ● Central attachment point: lowering attachment, positioning ropes for use in one mode, advance ropes and seat ● Lateral attachment points: Positioning rope connector for use in dual mode ● Rear belt anchorage point: Fastening the strap ● Certificates (S): CE EN 358, CE EN 813, UKCA, EAC ● Material: nylon, polyester, aluminum, steel ● Class II or III <p><u>Alpinistički pojas - 5 kom</u></p> <ul style="list-style-type: none"> ● Centralna točka pričvršćivanja: pričvršćivanje za spuštanje, užad za pozicioniranje za korištenje u jednom načinu rada, užad za napredovanje i sjedalo ● Bočne točke pričvršćivanja: Priključak za užad za pozicioniranje za korištenje u dvostrukom načinu rada ● Stražnja točka pričvršćivanja na pojasu: Pričvršćivanje trake za držanje ● Certifikati(S): CE EN 358, CE EN 813, UKCA, EAC ● Materijal: najlon, poliester, aluminij, čelik ● Klasa II ili III 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
61	<p><u>Alpinist helmet - 20 pcs</u></p> <ul style="list-style-type: none"> ● Head circumference: 53-63 cm ● Weight: 490 g ● Material (s): ABS (acrylonitrile butadiene styrene), nylon, polycarbonate, high strength polyester, polyethylene ● Certificates: CE, EN 397, EN 12492, ANSI Z89.1 Type I, class C, EAC <p><u>Alpinistička kaciga - 20 kom</u></p> <ul style="list-style-type: none"> ● Opseg glave: 53-63 cm ● Težina: 490 g ● Materijal (i): ABS (akrilonitril butadien stiren), najlon, polikarbonat, poliester visoke čvrstoće, polietilen ● Sertifikati: CE, EN 397, EN 12492, ANSI Z89.1 Tip I, klasa C, EAC 			

62	<p><u>Stop descender - 5 pcs</u></p> <ul style="list-style-type: none"> • the safety gate on the movable side panel allows easy installation of the rope while the device remains connected to the belt • AUTO-LOCK system • the movable side panel is locked with a screw, which allows I'D L to be integrated into the rescue kits • Stainless steel support plate improves durability by strengthening the friction zone of the rope • Lowering heavy loads up to 280 kg • Rope compatibility: 12.5 to 13 mm in diameter • Material (s): aluminum, steel, nylon • Weight: 600 g • Maximum working load for one person: 150 kg • Maximum working load for two people (rescue): 280 kg • Certificates: EN 341 type 2 class A, CE EN 12841 type C, ANSI Z359.4, NFPA 1983 • General use, EAC - EN 341 type 2 class A when used with rope VECTOR 12.5 mm - EN 12841 type C when used with rope from 12.5 to 13 mm EN 1891 A - ANSI Z359.4 when used with 12.5 to 13 mm rope - NFPA 1983 General use when used with 12.5 to 13 mm rope • Color red • Rope compatibility 12.5 to 13 mm <p><u>Stop descender - 5 kom</u></p> <ul style="list-style-type: none"> • sigurnosna kapija na pokretnoj bočnoj ploči omogućuje jednostavnu ugradnju užeta dok uređaj ostaje spojen na pojas • AUTO-LOCK sustav • pokretna bočna ploča zaključava se vijkom, što omogućuje integriranje I'D L u komplete za spašavanje • Nosiva ploča od nehrđajućeg čelika poboljšava izdržljivost ojačavajući zonu trenja užeta • Spuštanje teškog tereta do 280 kg • Kompatibilnost užeta: promjera 12,5 do 13 mm • Materijal(i): aluminij, čelik, najlon • Težina: 600 g • Maksimalno radno opterećenje za jednu osobu: 150 kg • Maksimalno radno opterećenje za dvije osobe (spasavanje): 280 kg • Certifikati: EN 341 tip 2 klasa A, CE EN 12841 tip C, ANSI Z359.4, NFPA 1983 			
----	---	--	--	--

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
	<ul style="list-style-type: none"> • Opća upotreba, EAC - EN 341 tip 2 klasa A kada se koristi s užetom VECTOR 12,5 mm - EN 12841 tip C kada koristi se s užetom od 12,5 do 13 mm EN 1891 A - ANSI Z359.4 kada se koristi s užetom od 12,5 do 13 mm - NFPA 1983 Opća upotreba kada se koristi s užetom od 12,5 do 13 mm • Boja crvena • Kompatibilnost užeta 12,5 do 13 mm 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
63	<p><u>Oval carabiner - 20 pcs</u></p> <ul style="list-style-type: none"> • screw door lock • Rough notches on the locking sleeve for easy handling • the trapped rod holds the carabiner in its correct orientation; the bar is easily removed with a Allen key no. 2 • slanted nose without jamming Keylock for smooth cutting and unbuttoning • Color gold, black • Weight 76 g • 2.68 oz • Light alloy material (anodized) • Main axis strength 26 kN • Strength lower axis 8 kN • Open door power 7 kN • Door opening (d) 21 mm • EN 362EN 12275ce1019 <p><u>Karabiner ovalni - 20 kom</u></p> <ul style="list-style-type: none"> • vijčano zaključavanje vrata • grubi zarezi na rukavcu za zaključavanje za jednostavnu manipulaciju • zarobljena šipka drži karabiner u njegovoj ispravnoj orijentaciji; šipka se lako uklanja pomoću imbus ključa br. 2 • ukošen nos bez zaglavljivanja Keylock za glatko šišanje i otkopčavanje • Boja zlatna, crna • Težina 76 g • 2,68 oz • Materijal laka legura (eloksirana) • Čvrstoća glavne osi 26 kN • Čvrstoća manja os 8 kN • Snaga otvorenih vrata 7 kN • Otvor vrata (d) 21 mm • EN 362EN 12275ce1019 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
64	<p><u>Oval carabiner - 20 pcs</u></p> <ul style="list-style-type: none"> ● Oval carabiner designed for use with pulleys, lifters and descents. ● screw door lock ● Nose lock ● Color blue, black ● Weight 80 g • 2.82 oz ● Light alloy material (anodized) ● Main axis strength 26 kN ● Strength less than 10 kN ● Open door power 7 kN ● Door opening (d) 21 mm ● EN 362EN 12275ce1019 <p><u>Karabiner ovalni - 20 kom</u></p> <ul style="list-style-type: none"> ● Ovalni karabiner dizajniran za korištenje s remenicama, podizačima i silaznima. ● vijčano zaključavanje vrata ● Nos za ključavnic ● Boja plava, crna ● Težina 80 g • 2,82 oz ● Materijal laka legura (eloksirana) ● Čvrstoća glavne osi 26 kN ● Čvrstoća manja os 10 kN ● Snaga otvorenih vrata 7 kN ● Otvor vrata (d) 21 mm ● EN 362EN 12275ce1019 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
65	<p><u>Alpinist rope - 1 pc</u></p> <ul style="list-style-type: none"> ● Rope diameter (mm) 9 ● Length: 100m ● Weight (g / m) 39.8 ● Min. power (daN) 1640 ● CE 1019 ● EN 564 <p><u>Alpinistički konopac - 1 kom</u></p> <ul style="list-style-type: none"> ● Dijametar konopca(mm) 9 ● Dužina: 100m ● Težina (g/m) 39.8 ● Min. snaga (daN) 1640 ● CE 1019 ● EN 564 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
66	<p><u>Static rope - 1 pc</u></p> <ul style="list-style-type: none"> • Minimum breaking strength in the figure of eight: 22 kN • Diameter: 11.80 mm • Length: 100 m • Basic share: 53% • Knotability: 0.80 • Sheath content: 47% • Weight per meter: 96 g / m • H20 shrinkage: 0.80% • Static elongation: 1.9% • Minimum breaking strength: 40 kN • Certification: EN 1891 Type A • Certificate: ANSI Z133 • Material: polyester / polyamide <p><u>Statički konopac - 1 kom</u></p> <ul style="list-style-type: none"> • Minimalna prekidna čvrstoća u čvoru osmice: 22 kN • Promjer: 11,80 mm • Dužina: 100 m • Temeljni udio: 53 % • Knotability: 0,80 • Udio omotača: 47 % • Težina po metru: 96 g/m • Skupljanje H20: 0,80 % • Statičko istezanje: 1,9 % • Minimalna prekidna čvrstoća: 40 kN • Certifikacija: EN 1891 Tip A • Certifikat: ANSI Z133 • Materijal: poliester/poliamid 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
67	<p><u>Static rope - pcs 1</u></p> <ul style="list-style-type: none"> • Diameter (mm) 10.2 • Weight (g / m) 60 • Length: 100 m • Relative envelope mass (%) 47 • Sheath slip (%) 0 • Elongation (50 - 150 kg) (%) 2.6 • Shrinkage (%) 0 • Endurance (kN) 23 • Min. endurance with knot (kN) 12 • Used PA / PPV sheath / core material • CE 1019 • EN 1891 <p><u>Statički konopac - kom 1</u></p> <ul style="list-style-type: none"> • Promjer (mm) 10.2 • Težina (g/m) 60 • Dužina: 100 m • Relativna masa omotača (%) 47 • Proklizavanje omotača (%) 0 • Elongacija (50 - 150 kg) (%) 2.6 • Skupljanje (%) 0 • Izdržljivost (kN) 23 • Min. izdržljivost sa čvorom (kN) 12 • Korišteni materijal PA / PPV plašt / jezgra • CE 1019 • EN 1891 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komisije za ocjenjivanje
68	<p><u>Strap joined - 10 pcs</u></p> <ul style="list-style-type: none"> ● Open loop anchor strap ● Length: 150 cm ● Material (s): polyester ● Breaking strength: 22 kN ● Certificates: CE EN 566, CE EN 795 B, EAC ● Weight: 80 g <p><u>Gurtna spojena - 10 kom</u></p> <ul style="list-style-type: none"> ● Remen sa otvorenom petljom za postavljanje sidra ● Dužina: 150 cm ● Materijal (i): poliester ● Prekidna čvrstoća: 22 kN ● Sertifikati: CE EN 566, CE EN 795 B, EAC ● Težina: 80 g 			
69	<p><u>Chest climber - 6 pcs</u></p> <ul style="list-style-type: none"> ● Chest rope clamp ● Material (s): aluminum, stainless steel, nylon ● Certificates: CE EN 567, CE EN 12841 type B, EAC, NFPA 1983 Technical use ● Weight: 140 g <p><u>Rope compatibility: 8 to 13 mm</u></p> <p><u>Prsna penjalica - 6 kom</u></p> <ul style="list-style-type: none"> ● Stezaljka za konopac za grudni koš ● Materijal (i): aluminijum, nerđajući čelik, najlon ● Sertifikati: CE EN 567, CE EN 12841 tip B, EAC, NFPA 1983 Tehnička upotreba ● Težina: 140 g ● Kompatibilnost konopca: 8 do 13 mm 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
70	<p><u>Pulley - 10 pcs</u></p> <ul style="list-style-type: none"> • Designed for heavy-duty handling or intensive use • Large diameter guard mounted on sealed ball bearings for excellent efficiency • Accepts up to three carabines for ease of use • Rope compatibility: 7 to 13 mm • Pulley diameter: 38 mm • Ball bearings • Maximum working load: 4 kN x 2 = 8 kN • Weight: 185 g • Certificates: CE EN 12278, NFPA 1983 General use • Color: red <p><u>Koturača - 10 kom</u></p> <ul style="list-style-type: none"> • Dizajnirano za rukovanje velikim opterećenjima ili za intenzivnu upotrebu • Štitnik velikog prečnika montiran na zapečaćenim kugličnim ležajevima za odličnu efikasnost • Prihvata do tri karabina za lakšu upotrebu • Kompatibilnost kanapa: 7 do 13 mm • Prečnik kotura: 38 mm • Kuglični ležajevi • Maksimalno radno opterećenje: 4 kN x 2 = 8 kN • Težina: 185 g • Sertifikati: CE EN 12278, NFPA 1983 Opšta upotreba • Boja: crvena 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
71	<p><u>Hand-held climber right - 5 pieces</u></p> <ul style="list-style-type: none"> • The climbing rope clamp must have a folded handle and an ergonomic upper for a comfortable and powerful grip when pulling with one or two hands. The rope clamp needs to have a wide lower opening for easy attachment of two carabiners to the belt and sock. • Material (s): aluminum, stainless steel, plastic, rubber, nylon • Weight: 165 g • Rope compatibility: 8 to 13 mm • Certificates: CE EN 567, CE EN 12841 type B, EAC, NFPA 1983 Technical use • Version: right • Color: yellow <p><u>Ručna penjalica desna - 5 kom</u></p> <ul style="list-style-type: none"> • Stezaljka konopca za penjanje uz konopac mora sadržavati preklopljeni rukohvat i ergonomski gornji dio za udoban i moćan zahvat pri povlačenju sa jednom ili dvije ruke. Stezaljka konopca potrebno da ima široki donji otvor za lako pričvršćivanje dva karabina za remen i nogavicu. • Materijal (i): aluminijum, nerđajući čelik, plastika, guma, najlon • Težina: 165 g • Kompatibilnost kanapa: 8 do 13 mm • Sertifikati: CE EN 567, CE EN 12841 tip B, EAC, NFPA 1983 Tehnička upotreba • Verzija: desna • Boja: žuta 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
72	<p><u>Electric pneumatic hammer - 1 pc</u></p> <ul style="list-style-type: none"> ● Battery voltage 18 V XR Li-Ion ● Battery capacity 4.0 Ah ● Number of batteries 2 pcs. ● Impact energy, max. 2.1 J. ● Led light ● Side handle ● Idle speed 1200 rpm ● Number of strokes in min 0 - 4,500 min-1 ● Weight including 3.1 kg battery ● SDS plus or equivalent tool acceptance ● XR charger ● PVC suitcase for storage and transport <p><u>Električni pneumatski čekić - 1 kom</u></p> <ul style="list-style-type: none"> ● Napon akumulatora 18 V XR Li-Ion ● Kapacitet akumulatora 4,0 Ah ● Broj akumulatora 2 kom. ● Energija udarca, maks. 2,1 J ● Led svjetlo ● Bočna drška ● Broj obrtaja u slobodnom hodu 1200 obr/min ● Broj udaraca u min 0 – 4,500 min-1 ● Masa uključujući bateriju 3.1 kg ● Prihvata alata SDS plus ili ekvivalent ● Punjač XR ● PVC kofer za spremanje i transport 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
73	<p><u>Descender A-B- 5 pcs</u> Rope diameter range (mm): 10.5 - 12.5</p> <ul style="list-style-type: none"> ● Panic brake: Yes ● Number of persons: 2 ● Finishing: anodized ● Certificates: EN 12841-B <p><u>Descender A-B- 5 kom</u> Raspon promjera užeta (mm): 10,5 - 12,5</p> <ul style="list-style-type: none"> ● Panik kočnica: Da ● Broj osoba: 2 ● Završna obrada: eloksirana ● Certifikati: EN 12841-B 			
74	<p><u>Descender - 10 pcs</u> <ul style="list-style-type: none"> ● Weight: 89g ● Breaking load: 25kN ● Rope diameters: Ø 8, mm - Ø 11 mm ● Length: 120 mm ● Material: aluminum <u>Descender - 10 kom</u> <ul style="list-style-type: none"> ● Težina: 89g ● Prekidno opterećenje: 25kN ● Promjeri užeta: Ø 8, mm - Ø 11 mm ● Duljina: 120 mm ● Materijal: aluminij </p>			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
75	<p><u>Double pulley - 4 pcs</u></p> <ul style="list-style-type: none"> ● Rope compatibility: 7 to 11 mm ● Shaft diameter: 25 mm ● Ball bearings: yes ● Efficiency: 91% ● Maximum working load: 2 x 1.5 kN x 2 = 6 kN ● Weight: 135 g ● <u>Certificates: EN 12278, NFPA 1983 Technical use</u> <p><u>Dupla kolutara - 4 kom</u></p> <ul style="list-style-type: none"> ● Kompatibilnost užeta: 7 do 11 mm ● Promjer osovine: 25 mm ● Kuglični ležajevi: da ● Učinkovitost: 91 % ● Maksimalno radno opterećenje: 2 x 1,5 kN x 2 = 6 kN ● Težina: 135 g ● Certifikati: EN 12278, NFPA 1983 Tehnička upotreba 			
76	<p><u>Panel mounting plate - 2 pcs</u></p> <ul style="list-style-type: none"> ● 19 mm holes ● Material (s): aluminum ● Certifications: NFPA 1983 General Use ● Color (s): yellow ● Weight: 180g ● Breaking strength: 45 kN <p><u>Ploča za pričvršćivanje "Šapa" - 2 kom</u></p> <ul style="list-style-type: none"> ● Rupe od 19 mm ● Materijal(i): aluminij ● Certifikati: NFPA 1983 Opća upotreba ● Boja(e): žuta ● Težina: 180g ● Prekidna čvrstoća: 45 kN 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
77	<p><u>Double pulley for zip line - 2 pcs</u></p> <ul style="list-style-type: none"> ● Accepts up to three carabines for ease of use ● Rope compatibility: diameter: 13 mm or less ● Shaft diameter: 21 mm ● Ball bearings: no ● Efficiency: 71% ● Maximum working load: 10 kN ● Weight: 195 g ● Certificates: EN 12278 <p><u>Dupla kolutara za zip line - 2 kom</u></p> <ul style="list-style-type: none"> ● Prihvaća do tri karabina radi lakšeg korištenja ● Kompatibilnost užeta: promjer: 13 mm ili manje ● Promjer osovine: 21 mm ● Kuglični ležajevi: br ● Učinkovitost: 71 % ● Maksimalno radno opterećenje: 10 kN ● Težina: 195 g ● Certifikati: EN 12278 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
78	<p><u>Rope protection - 5 pcs</u></p> <ul style="list-style-type: none"> • Three-layer construction for a high level of rope protection • Aramid middle layer • Layers marked with colors • Rope binding allows installation at any point along the length of the rope • Large eyelets • From 50cm to 80cm in length. <p><u>Zaštita za uže - 5 kom</u></p> <ul style="list-style-type: none"> • Troslojna konstrukcija za visoku razinu zaštite užeta • Aramidni srednji sloj • Slojevi označeni bojama • Vezivanje u užetu omogućuje instalaciju na bilo kojoj točki duž duljine užeta • Velike spojne ušice • Od 50cm do 80cm duljine. 			
79	<p><u>Rope in a reel - 2 pcs</u></p> <ul style="list-style-type: none"> • Diameter: 8 mm • Breaking load: 20 kN • Weight: 54.3 g / m • Materials: PES / Technora ili equivalent • EN 566, UIAA • Length: 50 m <p><u>Uže u kolutu - 2 kom</u></p> <ul style="list-style-type: none"> • Promjer: 8 mm • Prekidno opterećenje: 20 kN • Težina: 54,3 g/m • Materijali: PES/Technora ili ekvivalent • EN 566, UIAA • Duljina: 50 m 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
80	<p><u>Rope in a reel - 2 pcs</u></p> <ul style="list-style-type: none"> ● Diameter: 6-7 mm ● Breaking load: 20 kN ● Weight: 54.3 g / m ● Materials: PES / Technora or equivalent ● EN 566, UIAA ● Length: 100m <p><u>Uže u kolutu - 2 kom</u></p> <ul style="list-style-type: none"> ● Promjer: 6-7 mm ● Prekidno opterećenje: 20 kN ● Težina: 54,3 g/m ● Materijali: PES/Technora ili ekvivalent ● EN 566, UIAA ● Duljina: 100m 			

1. Item number / Broj	2. Specifications required / Tražena specifikacija	3. Specifications offered - with picture / Ponudena specifikacija - fotografija	4. Notes, remarks, ref to documentation / Zabilješke, primjedbe vezane za dokumentaciju	5. Evaluation committee's notes / Zabilješke Komsije za ocjenjivanje
81	<p><u>Burlap bag - 5 pcs</u></p> <ul style="list-style-type: none"> ● Padded shoulder straps for comfort ● Top cover with internal ID card pocket ● Coated fabric (without PVC) with welded construction for greater strength ● Lock with easy-to-handle lock, designed for harsh environments ● Side and top handles for carrying ● Upper pull-out loop ● Inner loop for hanging packages in the open position ● Weight: 850 g ● Volume: 30 liters ● Height: 65 cm ● Material (s): TPU, polyester <p><u>Vreća za užariju - 5 kom</u></p> <ul style="list-style-type: none"> ● Podstavljene naramenice za udobnost ● Gornji poklopac s unutarnjim džepom za identifikacijske kartice ● Obložena tkanina (bez PVC-a) sa zavarenom konstrukcijom za veću čvrstoću ● Zatvaranje s bravom s lakom za rukovanje, dizajnirano za teška okruženja ● Bočne i gornje ručke za ručno nošenje ● Gornja petlja za izvlačenje ● Unutarnja omča za vješanje paketa u otvorenom položaju ● Težina: 850 g ● Zapremina: 30 litara ● Visina: 65 cm ● Materijal(i): TPU, poliester 			

GENERAL INFORMATION / OPŠTE INFORMACIJE:

Warranty: 12 months / Garancija 12 mjeseci - Standard warranty / Delivery / Isporuca : Up to 90 days / do 90 dana

The technical characteristics specified in the specifications are considered as minimum requirements for tenderers. / Specificirane tehničke karakteristike se podrazumijevaju kao minimalni zahtjevi za ponuđače.

Service and spare parts provided in BiH and within a radius of 50 km / Servis i rezervni dijelovi moraju biti omogućeni u BiH u krugu od 50 km

Sizes will be defined additionally / Veličine će se definirati naknadno